FARO
BARCELONA


STUDIO 110 black pendant lamp
Ref. 28260 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	8
Light source	E14 LED
Bulb format	G45
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt Black

Installation instructions



STUDIO 110 black pendant lamp
Ref. 28260 |NAHTRANG

Recommended bulbs



Mat Bulb G45 LED E14 4W 2700K 450Lm

Reference	17461
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	4
Luminous Flux (lm)	390
Color temperature (K)	2700K
Opening angle degrees	360


STUDIO 110 white pendant lamp
Ref. 28261 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	8
Light source	E14 LED
Bulb format	G45
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt White

Installation instructions



STUDIO 110 white pendant lamp
Ref. 28261 |NAHTRANG

Recommended bulbs



Mat Bulb G45 LED E14 4W 2700K 450Lm

Reference	17461
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	4
Luminous Flux (lm)	390
Color temperature (K)	2700K
Opening angle degrees	360


STUDIO 110 pink pendant lamp
Ref. 28278 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	8
Light source	E14 LED
Bulb format	G45
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt Pink

Installation instructions



STUDIO 110 pink pendant lamp
Ref. 28278 |NAHTRANG

Recommended bulbs



Mat Bulb G45 LED E14 4W 2700K 450Lm

Reference	17461
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	4
Luminous Flux (lm)	390
Color temperature (K)	2700K
Opening angle degrees	360

FARO
BARCELONA


STUDIO 110 Blue pendant lamp
Ref. 28277 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	8
Light source	E14 LED
Bulb format	G45
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt Blue

Installation instructions



STUDIO 110 Blue pendant lamp
Ref. 28277 |NAHTRANG

Recommended bulbs



Mat Bulb G45 LED E14 4W 2700K 450Lm

Reference	17461
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	4
Luminous Flux (lm)	390
Color temperature (K)	2700K
Opening angle degrees	360

STUDIO 110 Blue pendant lamp
Ref. 28277 |NAHTRANG



FARO
BARCELONA


STUDIO 110 green pendant lamp
Ref. 28262 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	8
Light source	E14 LED
Bulb format	G45
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt Green

Installation instructions



STUDIO 110 green pendant lamp
Ref. 28262 |NAHTRANG

Recommended bulbs



Mat Bulb G45 LED E14 4W 2700K 450Lm

Reference	17461
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	4
Luminous Flux (lm)	390
Color temperature (K)	2700K
Opening angle degrees	360


STUDIO 160 black pendant lamp
Ref. 28263 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	15
Light source	E27 LED
Bulb format	A60
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt Black

Installation instructions



Recommended bulbs



Bulb A60 MAT LED E27 8W 2700K 640Lm

Reference	17463
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	800
Color temperature (K)	2700K
Opening angle degrees	360

FARO
BARCELONA


STUDIO 160 white pendant lamp
Ref. 28264 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	15
Light source	E27 LED
Bulb format	A60
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt White

Installation instructions



Recommended bulbs



Bulb A60 MAT LED E27 8W 2700K 640Lm

Reference	17463
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	800
Color temperature (K)	2700K
Opening angle degrees	360


STUDIO 160 green pendant lamp
Ref. 28265 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	15
Light source	E27 LED
Bulb format	A60
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt Green

Installation instructions



Recommended bulbs



Bulb A60 MAT LED E27 8W 2700K 640Lm

Reference	17463
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	800
Color temperature (K)	2700K
Opening angle degrees	360


STUDIO 160 pink pendant lamp
Ref. 28280 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	15
Light source	E27 LED
Bulb format	A60
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt Pink

Installation instructions



Recommended bulbs



Bulb A60 MAT LED E27 8W 2700K 640Lm

Reference	17463
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	800
Color temperature (K)	2700K
Opening angle degrees	360


STUDIO 160 Blue pendant lamp
Ref. 28279 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	15
Light source	E27 LED
Bulb format	A60
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt Blue

Installation instructions



Recommended bulbs



Bulb A60 MAT LED E27 8W 2700K 640Lm

Reference	17463
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	800
Color temperature (K)	2700K
Opening angle degrees	360

FARO
BARCELONA


STUDIO 290 black pendant lamp
Ref. 28283 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	15
Light source	E27 LED
Bulb format	G95
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt Black

Installation instructions



STUDIO 290 black pendant lamp
Ref. 28283 |NAHTRANG

Recommended bulbs



Bulb G95 MAT LED E27 8W 2700K 800Lm

Reference	17464
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	800
Color temperature (K)	2700K
Opening angle degrees	360

FARO
BARCELONA


STUDIO 290 white pendant lamp
Ref. 28284 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	15
Light source	E27 LED
Bulb format	G95
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt White

Installation instructions



Recommended bulbs



Bulb G95 MAT LED E27 8W 2700K 800Lm

Reference	17464
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	800
Color temperature (K)	2700K
Opening angle degrees	360

FARO
BARCELONA


STUDIO 290 Blue pendant lamp
Ref. 28286 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	15
Light source	E27 LED
Bulb format	G95
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt Blue

Installation instructions



Recommended bulbs



Bulb G95 MAT LED E27 8W 2700K 800Lm

Reference	17464
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	800
Color temperature (K)	2700K
Opening angle degrees	360


STUDIO 290 pink pendant lamp
Ref. 28287 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	15
Light source	E27 LED
Bulb format	G95
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt Pink

Installation instructions



STUDIO 290 pink pendant lamp
Ref. 28287 |NAHTRANG

Recommended bulbs



Bulb G95 MAT LED E27 8W 2700K 800Lm

Reference	17464
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	800
Color temperature (K)	2700K
Opening angle degrees	360

STUDIO 290 pink pendant lamp
Ref. 28287 |NAHTRANG



FARO
BARCELONA


STUDIO 290 green pendant lamp
Ref. 28285 |NAHTRANG

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	15
Light source	E27 LED
Bulb format	G95
Number of lamp holders	1
Light orientation	Direct
Cable length	2200 mm
Structure material	Steel
Shade material	Steel
Structure finish	Matt Black
Shade finish	Matt Green

Installation instructions



STUDIO 290 green pendant lamp
Ref. 28285 |NAHTRANG

Recommended bulbs



Bulb G95 MAT LED E27 8W 2700K 800Lm

Reference	17464
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	800
Color temperature (K)	2700K
Opening angle degrees	360

STUDIO 290 green pendant lamp
Ref. 28285 |NAHTRANG

