CAIRO Black portable beacon lamp
Ref. 74500


IP44




Mounting	Table
Voltage (V)	5VDC
Class	III
IP	44
Power (W)	2
Light source	SMD LED
Luminous Flux (lm)	120
Color temperature (K)	2700K
CRI	≥80
Switch type	Touch
Structure material	PC
Diffuser material	PC
Structure finish	Black
Diffuser finish	Transparent
Type of charge	Solar
Type of charging cable	USB-C
External device load output	SALIDA USB TIPO C
Battery included	Yes
Battery autonomy	6

Installation instructions

Photometric





FARO
BARCELONA

CAIRO Black portable beacon lamp
Ref. 74500



Document generated on 03/09/2026

CAIRO Sand portable beacon lamp
Ref. 74501


IP44




Mounting	Table
Voltage (V)	5VDC
Class	III
IP	44
Power (W)	2
Light source	SMD LED
Luminous Flux (lm)	120
Color temperature (K)	2700K
CRI	≥80
Switch type	Touch
Structure material	PC
Diffuser material	PC
Structure finish	Sand
Diffuser finish	Transparent
Type of charge	Solar
Type of charging cable	USB-C
External device load output	SALIDA USB TIPO C
Battery included	Yes
Battery autonomy	6

Installation instructions

Photometric





FARO
BARCELONA

CAIRO Sand portable beacon lamp
Ref. 74501

