PERLA Old gold wall lamp

Ref. 40085 |ALEX & MANEL LLUSCÀ

IP44



Mounting	Wall, Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	44
Power (W)	6
Light source	G9 LED
Number of lamp holders	1
Light orientation	Direct
Structure material	Steel
Diffuser material	Glass
Structure finish	Old Gold
Diffuser finish	Opal

Installation instructions



PERLA Old gold wall lamp
Ref. 40085 |ALEX & MANEL LLUSCÀ

Recommended bulbs



Bulb G9 LED 3,5W 2700K 350LM

Reference	17443
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	3,5
Luminous Flux (lm)	350
Color temperature (K)	2700K
Opening angle degrees	360

FARO
BARCELONA

PERLA Old gold wall lamp
Ref. 40085 |ALEX & MANEL LLUSCÀ



PERLA Chrome wall lamp
Ref. 40086 |ALEX & MANEL LLUSCÀ

IP44



Mounting	Wall, Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	44
Power (W)	6
Light source	G9 LED
Number of lamp holders	1
Light orientation	Direct
Structure material	Steel
Diffuser material	Glass
Structure finish	Chrome
Diffuser finish	Opal

Installation instructions



PERLA Chrome wall lamp
Ref. 40086 |ALEX & MANEL LLUSCÀ

Recommended bulbs



Bulb G9 LED 3,5W 2700K 350LM

Reference	17443
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	3,5
Luminous Flux (lm)	350
Color temperature (K)	2700K
Opening angle degrees	360

FARO
BARCELONA

PERLA Chrome wall lamp
Ref. 40086 |ALEX & MANEL LLUSCÀ



PERLA Bronze wall lamp

Ref. 40087 |ALEX & MANEL LLUSCÀ

IP44



Mounting	Wall, Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	44
Power (W)	6
Light source	G9 LED
Number of lamp holders	1
Light orientation	Direct
Structure material	Steel
Diffuser material	Glass
Structure finish	Bronze
Diffuser finish	Opal

Installation instructions



PERLA Bronze wall lamp
Ref. 40087 |ALEX & MANEL LLUSCÀ

Recommended bulbs



Bulb G9 LED 3,5W 2700K 350LM

Reference	17443
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	3,5
Luminous Flux (lm)	350
Color temperature (K)	2700K
Opening angle degrees	360

FARO
BARCELONA

PERLA Black wall lamp
Ref. 40088 |ALEX & MANEL LLUSCÀ

IP44



Mounting	Wall, Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	44
Power (W)	6
Light source	G9 LED
Number of lamp holders	1
Light orientation	Direct
Structure material	Steel
Diffuser material	Glass
Structure finish	Black
Diffuser finish	Opal

Installation instructions



Recommended bulbs



Bulb G9 LED 3,5W 2700K 350LM

Reference	17443
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	3,5
Luminous Flux (lm)	350
Color temperature (K)	2700K
Opening angle degrees	360