
GAS White recessed lamp
Ref. 43404



IP20

Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	8
Light source	GU10 LED
Bulb format	MR16
Number of lamp holders	1
Light orientation	Direct
Structure material	Aluminium
Structure finish	Matt White
Cut-out Size for Recessed Mount	ø76
Minimum Recessed Height (mm)	135
Maximum Ceiling Thickness (mm)	15
Includes recessed box	No

Installation instructions



GAS White recessed lamp
Ref. 43404

Recommended bulbs



Bulb GU10 LED 7W 2700K 38°

Reference	17316
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	7
Luminous Flux (lm)	632
Color temperature (K)	2700K
Opening angle degrees	38



Bulb GU10 LED 7,5W 2700K 60°

Reference	17320
Voltage (V)	100V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	705
Color temperature (K)	2700K
Opening angle degrees	60

Related accessories



GU10 BULB SOCKET for recessed

Reference	43065
IP	20
Structure material	Steel

FARO
BARCELONA

GAS White recessed lamp
Ref. 43404




GAS Black recessed lamp
Ref. 43405

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	8
Light source	GU10 LED
Bulb format	MR16
Number of lamp holders	1
Light orientation	Direct
Structure material	Aluminium
Structure finish	Matt Black
Cut-out Size for Recessed Mount	ø76
Minimum Recessed Height (mm)	135
Maximum Ceiling Thickness (mm)	15
Includes recessed box	No

Installation instructions



GAS Black recessed lamp
Ref. 43405

Recommended bulbs



Bulb GU10 LED 8W 2700K 60° BLACK

Reference	17324
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	629
Color temperature (K)	2700K
Opening angle degrees	60

Related accessories



GU10 BULB SOCKET for recessed

Reference	43065
IP	20
Structure material	Steel

FARO
BARCELONA

GAS Black recessed lamp
Ref. 43405




GAS 2L White recessed lamp
Ref. 43420

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	8
Light source	GU10 LED
Bulb format	MR16
Number of lamp holders	2
Light orientation	Direct
Structure material	Aluminium
Structure finish	Matt White
Cut-out Size for Recessed Mount	168x78
Minimum Recessed Height (mm)	135
Maximum Ceiling Thickness (mm)	15
Includes recessed box	No

Installation instructions



GAS 2L White recessed lamp
Ref. 43420

Recommended bulbs



Bulb GU10 LED 7W 2700K 38°

Reference	17316
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	7
Luminous Flux (lm)	632
Color temperature (K)	2700K
Opening angle degrees	38



Bulb GU10 LED 7,5W 2700K 60°

Reference	17320
Voltage (V)	100V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	705
Color temperature (K)	2700K
Opening angle degrees	60

Related accessories



GU10 BULB SOCKET for recessed

Reference	43065
IP	20
Structure material	Steel

FARO
BARCELONA

GAS 2L White recessed lamp
Ref. 43420



FARO
BARCELONA


GAS 2L Black recessed lamp
Ref. 43421

IP20



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	II
IP	20
Power (W)	8
Light source	GU10 LED
Bulb format	MR16
Number of lamp holders	2
Light orientation	Direct
Structure material	Aluminium
Structure finish	Matt Black
Cut-out Size for Recessed Mount	ø76
Minimum Recessed Height (mm)	135
Maximum Ceiling Thickness (mm)	15
Includes recessed box	No

Installation instructions



GAS 2L Black recessed lamp
Ref. 43421

Recommended bulbs



Bulb GU10 LED 7W 2700K 38°

Reference	17316
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	7
Luminous Flux (lm)	632
Color temperature (K)	2700K
Opening angle degrees	38



Bulb GU10 LED 7,5W 2700K 60°

Reference	17320
Voltage (V)	100V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	705
Color temperature (K)	2700K
Opening angle degrees	60

Related accessories



GU10 BULB SOCKET for recessed

Reference	43065
IP	20
Structure material	Steel