



Mito cosmo piano 20 datasheet

A ring-shaped recessed ceiling luminaire with double-sided light output and a diameter of 20 cm. There are two lighting effects to choose from: table (wide) for use above tables – expansive, glare-free light that is cast downwards and diffuse light pointed upwards (glowlight) – and room (narrow) as room luminaires to ensure perfect illumination for every use – concentrated, glare-free light aimed downwards and diffuse light pointed upwards (glowlight).

The luminaire head is set completely in the light channel that is flush with the ceiling. Version with plastering element and light channel for installation flush with the ceiling in hollow space ceilings, incl. power supply unit, connection to 230 V AC power supply. Controllable via Occhio air. The color temperature is continuously variable via Occhio air between 2700 – 4000 K (optional 2200 – 3500 K).



* cut-out dimensions mounting plate
incl. power supply unit (removable)

dimensions in mm



technical data Mito cosmo piano 20

| | | | |
|-------------------------|-----------------------------------------------|-------------------------------------------------------------------------------------------|--------------------------------------------|
| properties | material | aluminium, painted, PVD-coated steel, plastic, optical silicone, fibreglass | |
| | weight (luminaire + mounting plate) | 1.7 kg + 2.8 kg | |
| surface | head | bronze, matt gold, rose gold, matt silver, matt white, matt black, phantom, black phantom | |
| | light channel | matt white, matt gold | |
| Occhio »color tune« LED | average life time | > 50.000 hrs | |
| | energy efficiency class (luminous efficiency) | G (43 lm / W) | |
| | power | LED 20 W (incl. Occhio power supply unit 24 W, standby < 0.5 W) | |
| | color rendering index | high color; CRI Ra 95 | |
| | color temperature (color consistency) | 2700–4000 K (2-step) | 2200–3500 K (2-step 2200 K, 3-step 3500 K) |
| electricity | dimming | Occhio air | |
| | connection | 220–240 V AC | |
| | power factor power supply (cos φ1) | 0.95 | |
| | flicker / stroboscopic effect | < 1 (PstLM) / 0.4 (SVM) | |
| | permitted operating conditions | max. 30°C for indoor use only | |

* For a list of compatible dimmers, see www.occhio.com/dim_en

Mito cosmo piano 20 Support structure

The special substructure must be taken into account during planning due to the weight of the luminaire and should not deviate from the specified dimensions.



Mito cosmo piano 20 lighting effects







table (wide)

expansive light distributed downwards, light cone about 80° diffuse light pointed upwards (glowlight)

inserts: wide (down) / glow (up)

luminous flux : high color 20 W 850 lm

UGR (4H8H) < 19 *



room (narrow)

contentrated light distributed downwards, light cone about 50° diffuse light pointed upwards (glowlight)

inserts: narrow (down) / glow (up)

luminous flux : high color 20 W 720 lm

UGR (4H8H) < 19 *

*The standardized indication of glare values (UGR value – 4H8H) is not quite significant for annular luminaires. In most real applications the result of an individual calculation is a UGR value <19. Therefore, we recommend to carry out a calculation which can be prepared by our lighting design team (lightingdesign@occhio.de).