



Table lamp for indirect and diffused lighting. The 4 W LED source is housed in the base. The light intensity is adjustable through a 3 step (0 - 20 - 100%) touch dimmer. Aluminium structure and transparent glass diffuser.

## FINISHINGS

- Anodised Black
  - 3000K - cod. 14101XO00
  - 2700K - cod. 14101XOK27
- Anodised Brass
  - 3000K - cod. 14150XO00
  - 2700K - cod. 14150XOK27

ALL RAL COATING AND GALVANIC FINISHES AVAILABLE UPON REQUEST

## LIGHT EMISSION

Light source power: 4,2W	Efficacy 3000K: 12lm/W
Power absorption: 6W	Source Flux 2700K: 374lm@350mA
Light Emission: Diffuse	Emitted Flux 2700K: 70lm
Light Direction: Indirect Downlight	Efficacy 2700K: 12lm/W
Light Source: Discrete LED	CCT: 2700/3000K
Source Flux 3000K: 391lm@350mA	CRI: 90
Emitted Flux 3000K: 73lm	Lifetime: >55000h

## ELECTRICAL FACTS

Stand-by absorption: <0.5  
 Mains Voltage: 100/240VAC  
 Master output: 24VDC; max 0.63A  
 Ta max: 40°C

## PACKAGING DATA

Box dimensions: 21x21x27 cm  
 Volume: 0,012 m<sup>3</sup>  
 Gross weight: 1,7 kg

