

---

# Bols

ceiling light

---



---

## Table of contents

1. Product overview	Page 2
2. Finishes and materials	Page 2
3. Light Source & dimming	Page 2
4. Ordering codes	Page 3
5. Certifications & standards	Page 4
6. Maintenance & Cleaning	Page 4

---

## Versions



4023X  
Page 3

---

# Bols

ceiling light

---

## 1. Product overview

Outdoor aluminium ceiling light with polyethylene shade and integrated dimmable LED. Double layer coating for high resistance to corrosion and other maritime environmental conditions.



---

## 2. Finishes and Materials



**Shade:** Polyethylene

**Body:** 55 Beige

---

## 3. Light Source & Dimming

### Lamping

LED 10W (2700K / Ang. 120° / >90 CRI)

230V / Typ\* 870 lumens

\*Integrated LED module (included).

### Dimming options:

Standard: TRIAC

Optional: DALI, CASAMBI

# Bols

ceiling light

## 4. Ordering Codes

**Lamping**  
LED 10W (2700K / Ang. 120° / >90 CRI)  
230V / Typ\* 870 lumens  
\*Integrated LED module (included).

**DIM:** TRIAC (Optional DALI, CASAMBI)

**Finishes**  
55 Beige



Drawing	Mounting	Setting	Finish Body	Ordering Code
<p>BOL_4023X IP 65</p>	Ceiling light. Surface mounted.	Outdoor	Beige	BOL_4023X_55W

---

# Bols

ceiling light

---

## 5. Certifications & Standards



Warranty: 2 years

100% made in Spain

---

## 6. Maintenance & Cleaning

Our lighting fixtures are crafted with high-quality materials and finishes to ensure durability and timeless elegance. To maintain their original beauty, please follow these care recommendations:

1. Regular cleaning: Dust the fixture regularly using a soft, dry microfiber cloth to prevent buildup.
2. For deeper cleaning: If necessary, use a slightly damp cloth with clean water. Always dry the surface immediately with a dry cloth.
3. Avoid harsh products: Do not use alcohol, abrasive cleaners, solvents, or detergents, as they may damage the finish and alter the appearance.

In case of failure, LEDs can be easily replaced.