

## Globe

Globe ist die elegante Deckenleuchte aus Aluminium. Sie kombiniert formalen Minimalismus mit einer großzügigen optischen Linse und liefert ein warmes, gleichmäßiges und blendfreies Licht.

Globe eignet sich ideal für die Beleuchtung von Bädern, Eingangsbereichen oder Wohnräumen. Das hochwertige Design, die feinen Finishes und die brillante Lichtstimmung der LED-Deckenleuchte schaffen eine hochwertige Stimmung im Raum.

Designed und gefertigt am GRAU Campus in Deutschland.

---

## Farben

Farben	Artikelnummer
 Polished	SE22-0
 Sand White	SE22-5
 White	SE22-3
 Black	SE22-2

---

## Dimensionen



Head  
ø12 cm × H 8 cm

## Body

Maße Verpackung (L x B x H)	22cm x 22cm x 17cm
Material	Aluminium
Oberfläche	Pulverbeschichtet
Gewicht	0,9kg
Gewicht inkl. Verpackung	1,7kg
Montageart	Deckenaufbau
Nennspannung	220–240V
Leistungsaufnahme	12W
Leuchteneffizienz	78lm/W
Anschlussleitung (Ader-Zahl)	3
Schutzklasse	I
Artikelnummer	SE22-2

---

## Licht

Leuchtmittel	LED
Leuchtenlichtstrom	930lm
Farbwiedergabeindex	CRI >90
Lichtaustritt	Direkt
Abstrahlwinkel	97°
Lichtverteilung	Symmetrisch
Farbtemperatur	2700K
Lichtfarbe	Warmweiß
Dimmbar	Ja
Art der Dimmung	Phasenabschnitt

# GRAU

## Globe





Globe is the elegant aluminum ceiling light. It combines formal minimalism with a generous optical lens and provides a warm, uniform and glare-free light.

Globe is ideal for lighting bathrooms, entrance areas or living rooms. The high-quality design, the fine finishes and the brilliant lighting mood create a high-quality atmosphere in the room.

Designed and manufactured at the GRAU Campus in Germany.

---

## Colors

Colors	SKU
 Polished	SE22-0
 Sand White	SE22-5
 White	SE22-3
 Black	SE22-2

---

## Dimensions



Head  
ø12 cm × H 8 cm

## Body

Packaging dimensions (L x W x H)	22cm x 22cm x 17cm
Material	Aluminum
Surface	Powder-coated
Weight	0,9kg
Weight incl. packaging	1,7kg
Mounting type	Ceiling-mounted (surface)
Rated voltage	220–240V
Power consumption	12W
Luminaire efficiency	78lm/W
Connection cable (number of cores)	3
Protection class	I
SKU	SE22-2

---

## Light

Light source	LED
Luminous flux	930lm
Color rendering index	CRI >90
Light emission	Direct
Beam angle	97°
Light distribution	Symmetric
Color temperature	2700K
Light color	Warm White
Dimmable	Yes
Type of dimming	Trailing edge