

GRAU

Globe Wall 6

Globe Wall ist die feine Wandleuchte. Elegant im Design, schafft sie eine optisch entblendete Lichtverteilung nach oben und unten. Gefertigt in feinstem Aluminium, bringt sie hochwertige Stimmung in Bäder, Treppenhäuser, Flure und Wohnräume.

Mit Globe Wall werden Räume zu eleganten Wohlfühlorten. Montiere Globe Wall's minimalistische Form auf Augenhöhe und genieße die feine Lichtverteilung von zwei optischen Linsen, die das Licht der LED-Wandleuchte nach oben und unten an die Wand leuchten.

Designed und gefertigt am GRAU Campus in Deutschland.

Farben

Farben	Artikelnummer
 Sand White	CWA81-5
 Polished	CWA81-0
 Black	CWA81-1
 White	CWA81-3

Dimensionen

Head
7 cm × 14,8 cm × 6 cm



Linse
Ø 6 cm

Body

Material	Aluminium
Oberfläche	Pulverbeschichtet
Gewicht	0,9kg
Gewicht inkl. Verpackung	1kg
Montageart	Wandaufbau
Nennspannung	220–240V
Leistungsaufnahme	12W
Leuchteneffizienz	27lm/W
Anschlussleitung (Ader-Zahl)	3
Schutzklasse	I
Artikelnummer	CWA81-5

Licht

Leuchtmittel	LED
Leuchtenlichtstrom	325lm
Farbwiedergabeindex	CRI >90
Lichtaustritt	50% direkt / 50% indirekt
Lichtverteilung	Symmetrisch
Farbtemperatur	2700K
Lichtfarbe	Warmweiß
Dimmbar	Ja
Art der Dimmung	Phasenabschnitt

Globe Wall 6

Globe Wall is the fine wall light. Elegant in design, it creates an optically glare-free light distribution upwards and downwards. Made of the finest aluminum, it creates a high-quality atmosphere in bathrooms, stairwells, corridors and living rooms.

With Globe Wall, rooms become elegant places of well-being. Mount its minimalist shape at eye level and enjoy the fine light distribution of its two optical lenses, which shine the light upwards and downwards onto the wall.

Designed and manufactured at the GRAU Campus in Germany.

Colors

Colors	SKU
<div><div></div>Sand White</div>	CWA81-5
<div><div></div>Polished</div>	CWA81-0
<div><div></div>Black</div>	CWA81-1
<div><div></div>White</div>	CWA81-3

Dimensions



Body

Material	Aluminum
Surface	Powder-coated
Weight	0,9kg
Weight incl. packaging	1kg
Mounting type	Wall-mounted (surface)
Rated voltage	220–240V
Power consumption	12W
Luminaire efficiency	27lm/W
Connection cable (number of cores)	3
Protection class	I
SKU	CWA81-5

Light

Light source	LED
Luminous flux	325lm
Color rendering index	CRI >90
Light emission	50% direct / 50% indirect
Light distribution	Symmetric
Color temperature	2700K
Light color	Warm White
Dimmable	Yes
Type of dimming	Trailing edge