

Niceone Chandelier Three

Niceone Chandelier Three ist der minimale Lüster. Seine konische Form fließt perfekt in die optische Linse, die das Licht entblendet. Preisgekröntes Design, feinste Finishes und brillante Lichtstimmung – made in Germany.

Warm Dim passt beim Dimmen die Lichtfarbe automatisch an. Dimme das Licht per Drehdimmer oder GRAU App.

Designed und gefertigt am GRAU Campus in Deutschland.

Farben	Farben	Artikelnummer
	Black/Black	CNO03-1
	White/White	CNO03-3
	Polished/Grey	CNO03-0
	Raw/Charcoal	CNO03-8

Dimensionen



Body

Pendellänge	2m
Maße Verpackung (L x B x H)	60cm x 40cm x 20cm
Material	Aluminium
Oberfläche	Pulverbeschichtet
Gewicht	3,5kg
Gewicht inkl. Verpackung	5kg
Montageart	Deckenaufbau
Nennspannung	220–240V
Leistungsaufnahme	3x11W
Leuchteneffizienz	56lm/W
Anschlussleitung (Ader-Zahl)	3
Schutzklasse	I
Artikelnummer	CNO03-1

Licht

Leuchtmittel	LED
Leuchtenlichtstrom	3 x 620lm
Farbwiedergabeindex	CRI >90
Lichtaustritt	Direkt
Abstrahlwinkel	54°
Lichtverteilung	Symmetrisch
Farbtemperatur	2700–2200K
Lichtfarbe	Warmweiß
Dimmbar	Ja
Art der Dimmung	Phasenabschnitt
Warm Dim	Ja
GRAU App Upgrades möglich	Ja
Umbau auf DALI möglich	Ja

GRAU

Niceone Chandelier Three

Niceone Chandelier Three is the minimalist chandelier. Its conical shape flows perfectly into the optical lens, which reduces glare. Award-winning design, the finest finishes and brilliant mood lighting – made in Germany.

Warm Dim automatically adjusts the light color when dimming. Dim the light using a rotary dimmer or the GRAU app.

Designed and manufactured at the GRAU Campus in Germany.

Colors

Colors	SKU
Black/Black	CNO03-1
White/White	CNO03-3
Polished/Grey	CNO03-0
Raw/Charcoal	CNO03-8

Dimensions



Body

Pendant length	2m
Packaging dimensions (L x W x H)	60cm x 40cm x 20cm
Material	Aluminum
Surface	Powder-coated
Weight	3,5kg
Weight incl. packaging	5kg
Mounting type	Ceiling-mounted (surface)
Rated voltage	220–240V
Power consumption	3x11W
Luminaire efficiency	56lm/W
Connection cable (number of cores)	3
Protection class	I
SKU	CNO03-1

Light

Light source	LED
Luminous flux	3 x 620lm
Color rendering index	CRI >90
Light emission	Direct
Beam angle	54°
Light distribution	Symmetric
Color temperature	2700–2200K
Light color	Warm White
Dimmable	Yes
Type of dimming	Trailing edge
Warm Dim	Yes
GRAU App upgrades possible	Yes
Conversion to DALI possible	Yes