

GRAU


Simple

Simple ist einfach schön. Gefertigt in feinstem Aluminium, bringt Simple eine hochwertige Stimmung in Bäder, Treppenhäuser, Flure und Wohnräume. Mit Simple werden Räume zu eleganten Wohlfühlorten.

Montiere Simple's minimalistische Form auf Augenhöhe und genieße die feine Lichtverteilung von zwei optischen Linsen, die das Licht nach oben und unten an die Wand leuchten.

Designed und gefertigt am GRAU Campus in Deutschland.

Farben

Farben	Artikelnummer
 Sand White	CWA85-5
 White	CWA85-3
 Brass	CWA85-2
 Polished	CWA85-0

Dimensionen



Head
10 cm × 10 cm × 15,6 cm

Body

Maße Verpackung (L x B x H)	22cm x 24cm x 20cm
Material	Aluminium
Oberfläche	Poliert
Gewicht	1,4kg
Gewicht inkl. Verpackung	1,7kg
Montageart	Wandaufbau
Nennspannung	220–240V
Leistungsaufnahme	12W
Leuchteneffizienz	27lm/W
Anschlussleitung (Ader-Zahl)	3
Schutzklasse	I
Artikelnummer	CWA85-0

Licht

Leuchtmittel	LED
Leuchtenlichtstrom	325lm
Farbwiedergabeindex	CRI >90
Lichtaustritt	50% direkt / 50% indirekt
Abstrahlwinkel	91°
Lichtverteilung	Asymmetrisch
Farbtemperatur	2700K
Lichtfarbe	Warmweiß
Dimmbar	Ja
Art der Dimmung	Phasenabschnitt

GRAU

Simple

Simple is simply beautiful. Manufactured in the finest aluminum, it brings a high-quality atmosphere to bathrooms, stairwells, corridors and living rooms. Simple turns rooms into elegant places of well-being.

Mount its minimalist shape at eye level and enjoy the fine light distribution of its two optical lenses, which shine the light upwards and downwards onto the wall.

Designed and manufactured at the GRAU Campus in Germany.

Colors

Colors	SKU
 Sand White	CWA85-5
 White	CWA85-3
 Brass	CWA85-2
 Polished	CWA85-0

Dimensions



Head
10 cm × 10 cm × 15,6 cm

Body	Packaging dimensions (L x W x H)	22cm x 24cm x 20cm
	Material	Aluminum
	Surface	Polished
	Weight	1,4kg
	Weight incl. packaging	1,7kg
	Mounting type	Wall-mounted (surface)
	Rated voltage	220–240V
	Power consumption	12W
	Luminaire efficiency	27lm/W
	Connection cable (number of cores)	3
	Protection class	I
	SKU	CWA85-0

Light	Light source	LED
	Luminous flux	325lm
	Color rendering index	CRI >90
	Light emission	50% direct / 50% indirect
	Beam angle	91°
	Light distribution	Asymmetric
	Color temperature	2700K
	Light color	Warm White
	Dimmable	Yes
	Type of dimming	Trailing edge