

# GRAU

## Studio

Studio ist ein spielerisches und leistungsstarkes Strahlersystem mit unterschiedlichen Optionen für Wand und Decke. Passe die Blickrichtung der Leuchtenköpfe im hyperflexiblen Spielraum von 270° der Raum Architektur an.

Mit schönem Licht und glänzender Oberfläche setzt Studio vitale Akzente.

---

## Farben

Farben	Artikelnummer
Polished/White	SP00-1
Polished/Black	SP00-8
Satin/White	SP00-6
Satin/Black	SP00-2

---

## Dimensionen

Fixture  
Ø13,6 cm × 4,4 cm



Head  
11 cm × 11 cm

# GRAU

## Body

Maße Verpackung (L x B x H)	22cm x 24cm x 20cm
Material	Aluminium
Oberfläche	Lackiert
Gewicht	0,8kg
Gewicht inkl. Verpackung	1,3kg
Leuchtenkopf beweglich	Ja
Montageart	Deckenaufbau
Nennspannung	220–240V
Leistungsaufnahme	15W
Leuchteneffizienz	55lm/W
Anschlussleitung (Ader-Zahl)	2
Schutzklasse	II
Artikelnummer	SP00-2

---

## Licht

Leuchtmittel	LED
Leuchtenlichtstrom	830lm
Farbwiedergabeindex	CRI >90
Lichtaustritt	Direkt
Abstrahlwinkel	41°
Lichtverteilung	Symmetrisch
Farbtemperatur	2700K
Lichtfarbe	Warmweiß
Dimmbar	Ja
Art der Dimmung	Phasenabschnitt
GRAU App Upgrades möglich	Ja
Umbau auf DALI möglich	Ja

# GRAU

## Studio

Studio is a playful and powerful spotlight system with different options for wall and ceiling. Adapt the viewing direction of the luminaire heads in the hyper-flexible play of 270° to the space architecture.

With beautiful light and glossy finish, Studio sets vital accents.

---

## Colors

Colors	SKU
Polished/White	SP00-1
Polished/Black	SP00-8
Satin/White	SP00-6
Satin/Black	SP00-2

---

## Dimensions

Fixture  
Ø13,6 cm × 4,4 cm



Head  
11 cm × 11 cm

# GRAU

## Body

Packaging dimensions (L x W x H)	22cm x 24cm x 20cm
Material	Aluminum
Surface	Satined
Weight	0,8kg
Weight incl. packaging	1,3kg
Movable lamp head	Yes
Mounting type	Ceiling-mounted (surface)
Rated voltage	220–240V
Power consumption	15W
Luminaire efficiency	55lm/W
Connection cable (number of cores)	2
Protection class	II
SKU	SP00-2

---

## Light

Light source	LED
Luminous flux	830lm
Color rendering index	CRI >90
Light emission	Direct
Beam angle	41°
Light distribution	Symmetric
Color temperature	2700K
Light color	Warm White
Dimmable	Yes
Type of dimming	Trailing edge
GRAU App upgrades possible	Yes
Conversion to DALI possible	Yes