

# Tik

wall light




## Table of contents

1. Product overview	Page 2
2. Finishes and materials	Page 2
3. Light Source & dimming	Page 2
4. Installation	Page 3
5. Ordering codes	Page 4
6. Certifications & standards	Page 5
7. Maintenance & Cleaning	Page 5

## Versions



TIK\_4090X (Outdoor version)  
Page 4



TIK\_4090 (Indoor version)  
Page 4

# Tik

wall light

## 1. Product overview

Metallic wall-mounted lamp for accent or ambient lighting, available in indoor and outdoor versions.

The outdoor version features a PMMA diffuser with a 60° beam angle, while the indoor version includes an embedded aluminium optic lens with a 30° beam angle. Both models incorporate a dimmable integrated LED, providing direct light through a fixed cylindrical tube enclosing the light source.

Outdoor version: The remote driver must be installed in an IP65-rated box or indoors. Maximum cable length between driver and lamp: 17 meters.

Double-layer coating ensures high resistance to corrosion and maritime environmental conditions.



## 2. Finishes and Materials



88 Grey Stone (Outdoor and Indoor)

96 Anthracite (Outdoor and Indoor)

89 Pale Green (Outdoor Only)

61 Satin Gold (Indoor Only)

## 3. Light Source & Dimming

### Lamping (Outdoor):

LED 3W (2700K / Ang. 60° / >90 CRI / 24V)

100-240V / Typ 300 lumens

Optic lens: (PMMA) lens diffuser 60°.

\*Integrated LED module (included).

### Dimming options:

Standard: TRIAC

Optional: DALI

### Lamping (Indoor):

LED 6,2W (2700K / Ang. 30° / >90 CRI / 300mA)

230V / Typ 652 lumens

Optic lens: embedded aluminium optic lens 30°.

\*Integrated LED module (included).

### Dimming options:

Optional: DALI

## 4. Installation

### Outdoor

Recessed canopy with remote driver



Remote driver must be placed in IP 65 box or inside the home. Maximum distance from the driver to the lamps 17 meters.

### Indoor

Surface canopy



### 60° beam angle

Acrylic optic. It provides diffuse, uniform illumination and is visible as a decorative light line when viewed from the side.



### 30° beam angle

Architectural optic conceals the LED source within a conical aluminium lens. It projects light exclusively downward (no lateral emission).



## 5. Ordering Codes

### Lamping 4090X (Outdoor version)

LED 3W (2700K / Ang. 60° / >90 CRI / 24V)

100-240V / Typ 300 lumens

**Optic lens:** (PMMA) lens diffuser 60°.

**DIM:** TRIAC (Optional DALI)

### Finishes:

88 Grey Stone

89 Pale Green

96 Anthracite



Drawing	Mounting	Setting	Finish Body	Ordering Code
TIK_4090X IP65 	Recessed, remote driver	Outdoor	Grey Stone	TIK_4090X_88W
		Outdoor	Pale Green	TIK_4090X_89W
			Anthracite	TIK_4090X_96W

### Lamping 4090 (Indoor version)

LED 6,2W (2700K / Ang. 30° / >90 CRI / 300mA)

230V / Typ 652 lumens

**Optic lens:** embedded aluminium optic lens 30

**DIM:** Optional DALI

### Finishes:

61 Satin Gold

88 Grey Stone






96 Anthracite



Drawing	Mounting	Setting	Finish Body	Ordering Code
TIK_4090 IP20 	Wall lamp Surface mounted	Indoor	Satin Gold	TIK_4090_61W
		Indoor	Grey Stone	TIK_4090_88W
			Anthracite	TIK_4090_96W

## 6. Certifications & Standards

TIK\_4090X        

TIK\_4090        

Warranty: 2 years

100% made in Spain

---

## 7. Maintenance & Cleaning

Our lighting fixtures are crafted with high-quality materials and finishes to ensure durability and timeless elegance. To maintain their original beauty, please follow these care recommendations:

1. Regular cleaning: Dust the fixture regularly using a soft, dry microfiber cloth to prevent buildup.
2. For deeper cleaning: If necessary, use a slightly damp cloth with clean water. Always dry the surface immediately with a dry cloth.
3. Avoid harsh products: Do not use alcohol, abrasive cleaners, solvents, or detergents, as they may damage the finish and alter the appearance.

In case of failure, LEDs can be easily replaced.